


CD Series

Cold Water – Electric – Direct Drive

A great choice for all-purpose cleaning around a home or small business, the lightweight and portable design of the CD Electric Series makes it easy to use almost anywhere. It can tackle those quick cleaning jobs where a gas powered unit isn't needed.



CD-1502-3MUH



Pump:

Forged brass manifold (Nickel plated brass on 2MUH models) ■ Thermal and safety relief valves ■ Built-in low pressure detergent injector

Motor:

Totally enclosed fan-cooled electric motor with thermal overload protection ■ 35-foot, 15-amp power cord with GFCI (20-amp on CD-1502 models)

Frame:

Powder coated steel mounting plate with center balanced lift and four rubber isolators

Unit Includes:

Variable high/low pressure nozzles (3MUH models) ■ 15° high/low pressure nozzle (2MUH models) ■ 25-foot x 3/8-inch non-marking high pressure hose with quick connects ■ Professional-grade insulated trigger gun with safety lock-off

Limited Warranties:

1 year electric motor ■ 7 year AR and General pumps

Certification:

CSA Certified - US and Canada



MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CD-1002-3MUH	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	AR	3-0362	Adjustable pressure	NEMA 5-15P	36in.	20x11.5x14in.	70 lb.	58 lb.
CD-1002-2MUH*	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	General	3-0278	Adjustable pressure	NEMA 5-15P	36in.	20x11.5x14in.	71 lb.	66 lb.
CD-1502-3MUH	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	3-0362	Adjustable pressure	NEMA 5-20P	36in.	20x11.5x14in.	76 lb.	70 lb.
CD-1502-2MUH*	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	General	3-0278	Adjustable pressure	NEMA 5-20P	36in.	20x11.5x14in.	76 lb.	70 lb.

*Pump accepts incoming water up to 175°F.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
18-0370	Rotating nozzle	CD-1502 models	CX-0030	50-ft. x 3/8-in. non-marking high pressure hose	All models
18-0371	Rotating nozzle	CD-1002 models			
50-0161	High pressure detergent injector	All models			