

# JP Series

## Cold Water – Electric – Direct Drive

### Pump:

Forged brass manifold (Nickel plated brass on 2ME1 models) ■ Thermal and safety relief valves ■ Built-in low pressure detergent injector

### Motor:

Totally enclosed fan-cooled electric motor ■ 35-foot power cord with GFCI (1.5 to 6.0 HP single-phase models) (10-foot power cord on 8.0-HP models)

### Frame:

Powder coated steel frame and base plate with 1¼-inch tube handles ■ Convenient gun/wand holder and hose wrap ■ 13-inch flat-free tires (10-inch on JP-1002, JP-1502 and JP-2003 models)

### Unit Includes:

Variable high/low pressure nozzle (JP-1002, JP-1502 and JP-2003 models) ■ Quick connect nozzles - 0°, 15° and 25° (JP-2503 and JP-3004 models) ■ 50-foot x ¾-inch non-marking high pressure hose with quick connects (25-foot on JP-1002, JP-1502 and JP-2003 models) ■ Professional-grade trigger gun with safety lock-off

### Limited Warranties:

1 year electric motor ■ 7 year AR and General pumps


### Certification:

CSA Certified - US and Canada (JP-1002 and JP-1502 models) ■ CSA Certified - US only (JP-2003, JP-2503 and JP-3004 models)

This is the perfect tool for food and beverage processing facilities where fumes and smoke are prohibited. Contractors love the versatility of the JP Series electric pressure washer to tackle indoor jobs along with those tough outdoor cleaning tasks.



JP-1002-3ME1



NEMA 5-15P, 15-amp plug   NEMA 5-20P, 20-amp plug   NEMA L15-20P, 20-amp plug   NEMA 6-20P, 20-amp plug   NEMA L15-30P, 30-amp plug   NEMA 6-30P, 30-amp plug   NEMA 6-50P, 50-amp plug

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-1002-3ME1	1000	2.0	1.5 HP, 120V, 10, 15.0A	AR	3-0362	Adjustable pressure	NEMA 5-15P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1002-2ME1*	1000	2.0	1.5 HP, 120V, 10, 15.0A	General	3-0278	Adjustable pressure	NEMA 5-15P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1502-3ME1	1500	2.0	2.0 HP, 120V, 10, 17.0A	AR	3-0362	Adjustable pressure	NEMA 5-20P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1502-2ME1*	1500	2.0	2.0 HP, 120V, 10, 17.0A	General	3-0278	Adjustable pressure	NEMA 5-20P	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-2003-3ME1	2000	2.6	4.0 HP, 230V, 10, 16.0A	AR	3-0364	Adjustable pressure	NEMA 6-20P	36in.	37x21x24.5in.	162 lb.	112 lb.
JP-2503-1ME1	2500	3.2	6.0 HP, 230V, 10, 24.1A	AR	3-0307	Adjustable pressure	NEMA 6-30P	36in.	44x26x27in.	275 lb.	225 lb.
JP-2503-0ME3	2500	3.2	6.0 HP, 230V, 30, 15.0A or 6.0 HP, 460V, 30, 7.5A	AR	3-0307	Adjustable pressure	NEMA L15-20P	36in.	44x26x27in.	275 lb.	225 lb.
JP-3004-1ME1	3000	3.9	8.0 HP, 230V, 10, 34.5A	AR	3-0207	Adjustable pressure	NEMA 6-50P	36in.	44x26x27in.	275 lb.	225 lb.
JP-3004-0ME3	3000	3.9	8.0 HP, 230V, 30, 20.0A or 8.0 HP, 460V, 30, 10.0A	AR	3-0207	Adjustable pressure	NEMA L15-30P	36in.	44x26x27in.	275 lb.	225 lb.

\*Pump accepts incoming water up to 175°F.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0066	460V on 6.0-HP, 3-phase model	JP-2503-0ME3
CX-0005	36-in. insulated dual lance	All models	CX-0067	460V on 8.0-HP, 3-phase model	JP-3004-0ME3
CX-0030	50-ft. x ¾-in. non-marking high pressure hose	1000 to 2000-PSI models			